

**AD**

**SPECIAL PUBLICATION ARCCB-SP-03007**

**INDEX TO BENET LABORATORIES  
TECHNICAL REPORTS - 2002**

**R. D. SHUMAN**

**APRIL 2003**



TACOM-ARDEC

US ARMY ARMAMENT RESEARCH,  
DEVELOPMENT AND ENGINEERING CENTER  
Close Combat Armaments Center  
Benét Laboratories  
Watervliet, NY 12189-4000



**APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED**

**20030606 093**

## **DISCLAIMER**

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

The use of trade name(s) and/or manufacturer(s) does not constitute an official endorsement or approval.

## **DESTRUCTION NOTICE**

For classified documents, follow the procedures in DoD 5200.22-M, Industrial Security Manual, Section II-19, or DoD 5200.1-R, Information Security Program Regulation, Chapter IX.

For unclassified, limited documents, destroy by any method that will prevent disclosure of contents or reconstruction of the document.

For unclassified, unlimited documents, destroy when the report is no longer needed. Do not return it to the originator.

## REPORT DOCUMENTATION PAGE

*Form Approved  
OMB No. 0704-0188*

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE April 2003	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE INDEX TO BENET LABORATORIES TECHNICAL REPORTS - 2002		5. FUNDING NUMBERS N/A	
6. AUTHORS R.D. Shuman			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000		8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-SP-03007	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT ( <i>Maximum 200 words</i> ) This is a compilation of technical reports published by Benet Laboratories in 2002.			
14. SUBJECT TERMS Benet Laboratories, Technical Publications, Bibliographies, Abstracts, Document Control Data		15. NUMBER OF PAGES 28	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

## **TABLE OF CONTENTS**

	<u>Page</u>
LIST OF REPORTS.....	1
AUTHOR INDEX.....	3
SUBJECT INDEX.....	5
AD NUMBERS.....	10
REPORT DOCUMENTATION PAGES.....	11

## TECHNICAL REPORTS 2002

REPORT NUMBER	TITLE	AUTHOR	DATE
ARCCB-TR-02001	Sonic Rarefaction Wave Low Recoil Gun	E. Kathe R. Dillon	Jan 02
ARCCB-TR-02002	Gun Barrel Vibration Absorber to Increase Accuracy	A. Littlefield E. Kathe R. Messier K. Olsen	Feb 02
ARCCB-TR-02003	Adaptive Gun Barrel Vibration Absorber	A. Littlefield E. Kathe	Mar 02
ARCCB-TR-02004	Evaluation of University of Tennessee Space Institute's Laser-Induced Surface Improvement (LISI) Technique for Gun Bore Protection	G. Kendall P.J. Cote M. Todaro F. Yee C. Rickard	Mar 02
ARCCB-SP-02005	Index to Benet Laboratories Technical Reports - 2002	R.D. Shuman	Apr 02
ARCCB-TR-02006	Yield Pressure Measurements and Analysis for Autofrettaged Cannons	J.H. Underwood D.B. Moak M.A. Audino A.P. Parker	May 02
ARCCB-TR-02007	A Fire Out-of-Battery Tank Gun: Theory and Simulation	E. Kathe R. Gast	May 02
ARCCB-TR-02008	An Algorithm for the Determination of Coating Properties from Laser-Generated and Detected Rayleigh Waves Using Wavelet Analysis: Application to Sputtered Tantalum	M.A. Doxbeck M.A. Hussain J. Rama A. Abbate J. Frankel	Jul 02
ARCCB-TR-02009	Characterization of Steels Using a Revised Kinetic Hardening Model Incorporating Bauschinger Effect	A.P. Parker E. Troiano J.H. Underwood C. Mossey	Aug 02
ARCCB-TR-02010	Dynamically Tuned Shroud for Attenuating Gun Barrel Vibration	A.G. Littlefield E. L. Kathe R. Durocher	Aug 02
ARCCB-TR-02011	Evolution of Surface Structures in Sputtered Coatings	M.A. Johnson P.J. Cote	Aug 02
ARCCB-TR-02012	Detrended Fluctuation Analysis of UV Degradation in a Polyurethane Coating	M.A. Johnson P.J. Cote	Aug 02
ARCCB-TR-02013	Safe Maximum Pressure Determination for the M829E3/M256 Cannon Qualification Program	D.C. Smith E.E. Coppola	Sep 02

## TECHNICAL REPORTS 2002

ARCCB-TR-02014	<i>In-Situ</i> Phase Evolution Study in Magnetron-Sputtered Tantalum Thin Films	S.L. Lee D. Windover T.-M. Lu M. Audino	Oct 02
ARCCB-TR-02015	Main Battle Tank Flexible Gun Tube Disturbance Model: Three-Segment Model	H.J. Sneck	Oct 02
ARCCB-TR-02016	Characterization of Explosively Bonded and Fired Tantalum Liners Applied to 25-mm Gun Tubes	C. Mulligan M. Audino P. Cote G. Kendall C. Rickard S. Smith M. Todaro	Nov 02
ARCCB-TR-02017	Updated Erosion Modeling Predictions for the M829E3 Round	S. Sopok G. Pflegl C. Rickard	Dec 02

## **AUTHOR INDEX 2002**

<b>AUTHOR</b>	<b>REPORT NUMBER</b>
Abbate, A.	ARCCB-TR-02008
Audino, M.A.	ARCCB-TR-02006 ARCCB-TR-02014 ARCCB-TR-02016
Coppola, E.E.	ARCCB-TR-02013
Cote, P.J.	ARCCB-TR-02004 ARCCB-TR-02011 ARCCB-TR-02012 ARCCB-TR-02016
Dillon, R.	ARCCB-TR-02001
Doxbeck, M.A.	ARCCB-TR-02008
Durocher, R.	ARCCB-TR-02010
Frankel, J.	ARCCB-TR-02008
Gast, R.	ARCCB-TR-02007
Hussain, M.A.	ARCCB-TR-02008
Johnson, M.A.	ARCCB-TR-02011 ARCCB-TR-02012
Kathe, E.L.	ARCCB-TR-02001 ARCCB-TR-02002 ARCCB-TR-02003 ARCCB-TR-02007 ARCCB-TR-02010
Kendall, G.	ARCCB-TR-02004 ARCCB-TR-02016
Lee, S.L.	ARCCB-TR-02014
Littlefield, A.G.	ARCCB-TR-02002 ARCCB-TR-02003 ARCCB-TR-02010

## AUTHOR INDEX 2002

Lu, T.-M.	ARCCB-TR-02014
Messier, R.	ARCCB-TR-02002
Moak, D.B.	ARCCB-TR-02006
Mossey, C.	ARCCB-TR-02009
Mulligan, C.	ARCCB-TR-02016
Olsen, K.	ARCCB-TR-02002
Parker, A.P.	ARCCB-TR-02006 ARCCB-TR-02009
Pflegl, G.	ARCCB-TR-02017
Rama, J.	ARCCB-TR-02008
Rickard, C.	ARCCB-TR-02004 ARCCB-TR-02016 ARCCB-TR-02017
Shuman, R.D.	ARCCB-SP-02005
Smith, D.C.	ARCCB-TR-02013
Smith, S.	ARCCB-TR-02016
Sneck, H.J.	ARCCB-TR-02015
Sopok, S.	ARCCB-TR-02017g
Todaro, M.	ARCCB-TR-02004 ARCCB-TR-02016
Troiano, E.	ARCCB-TR-02009
Underwood, J.H.	ARCCB-TR-02006 ARCCB-TR-02009
Windover, D.	ARCCB-TR-02014
Yee, F.	ARCCB-TR-02004

## **SUBJECT INDEX - 2002**

<b>SUBJECT</b>	<b>REPORT NUMBER</b>
A723 Steel	ARCCB-TR-02009
Absorbers (Equipment)	ARCCB-TR-02010
Abstracts	ARCCB-SP-02005
Accuracy	ARCCB-TR-02002 ARCCB-TR-02003 ARCCB-TR-02010
Algorithms	ARCCB-TR-02008
Autofrettage	ARCCB-TR-02006 ARCCB-TR-02009
Bauschinger Effect	ARCCB-TR-02006 ARCCB-TR-02009
Bibliographies	ARCCB-SP-02005
Bores	ARCCB-TR-02004
Cannons	ARCCB-TR-02006 ARCCB-TR-02010 ARCCB-TR-02013
Chromium	ARCCB-TR-02004
Coatings	ARCCB-TR-02004 ARCCB-TR-02008 ARCCB-TR-02011 ARCCB-TR-02012
Crusader	ARCCB-TR-02004
de Laval Nozzle	ARCCB-TR-02001
Detrended Fluctuation Analysis (DFA)	ARCCB-TR-02012
Dispersing	ARCCB-TR-02003

## **SUBJECT INDEX - 2002**

Dynamic Scaling Exponents	ARCCB-TR-02011
Dynamics	ARCCB-TR-02002 ARCCB-TR-02003 ARCCB-TR-02010
Elastic Modulus	ARCCB-TR-02009
Elastic Properties	ARCCB-TR-02013
Erosion	ARCCB-TR-02004 ARCCB-TR-02016 ARCCB-TR-02017
Explosive Bonding	ARCCB-TR-02016
Fatigue Life	ARCCB-TR-02009
Finite Element Analysis	ARCCB-TR-02013
Fire Out-of-Battery (FOOB)	ARCCB-TR-02007
Firing Tests (Ordnance)	ARCCB-TR-02002
Fractals	ARCCB-TR-02011 ARCCB-TR-02012
Future Combat System (FCS)	ARCCB-TR-02001 ARCCB-TR-02007
Gun Barrels	ARCCB-TR-02002 ARCCB-TR-02003 ARCCB-TR-02007 ARCCB-TR-02010
Gun Mounts	ARCCB-TR-02007
Gun Tubes	ARCCB-TR-02004 ARCCB-TR-02006 ARCCB-TR-02009 ARCCB-TR-02013 ARCCB-TR-02015 ARCCB-TR-02016

## **SUBJECT INDEX - 2002**

Guns	ARCCB-SP-02005 ARCCB-TR-02017
High-Strength Steel	ARCCB-TR-02006
Hydraulics	ARCCB-TR-02013
Image Analysis	ARCCB-TR-02012
Image Processing	ARCCB-TR-02011
Indexes	ARCCB-SP-02005
<i>In-Situ</i> Characterization	ARCCB-TR-02014
Interior Ballistics	ARCCB-TR-02001
Kinetic Hardening Model	ARCCB-TR-02009
Laser Surface Treatment	ARCCB-TR-02004
Lasers	ARCCB-TR-02008
Liners	ARCCB-TR-02016
Low Recoil Guns	ARCCB-TR-02001
M256 Guns	ARCCB-TR-02013 ARCCB-TR-02017
M829E3 Ammunition	ARCCB-TR-02017
Magnetron Sputtering	ARCCB-TR-02014
Mathematical Models	ARCCB-TR-02015
Niobium	ARCCB-TR-02011
Polyurethane Coatings	ARCCB-TR-02012
Pressure Measurements	ARCCB-TR-02013
Pressure Vessels	ARCCB-TR-02006 ARCCB-TR-02009

## **SUBJECT INDEX - 2002**

Projectiles	ARCCB-TR-02017
Propulsion	ARCCB-TR-02001
Protective Coatings	ARCCB-TR-02004
RArefaction waVE guNs (RAVEN)	ARCCB-TR-02001
Rayleigh Waves	ARCCB-TR-02008
Real-Time X-Ray Diffraction	ARCCB-TR-02014
Recoil Mechanisms	ARCCB-TR-02007
Recoilless Rifles	ARCCB-TR-02001
Refractory Coatings	ARCCB-TR-02016
Reports	ARCCB-SP-02005
Residual Stress	ARCCB-TR-02009
Safe Maximum Pressure (SMP)	ARCCB-TR-02013
Smart Structures	ARCCB-TR-02003
Soft Recoil	ARCCB-TR-02007
Sonic Rarefaction Waves	ARCCB-TR-02001
Sputtering	ARCCB-TR-02008 ARCCB-TR-02011 ARCCB-TR-02014
Stabilization Systems	ARCCB-TR-02015
Steel	ARCCB-TR-02009
Strain Hardening	ARCCB-TR-02009
Strain Rate	ARCCB-TR-02013
Structural Properties	ARCCB-TR-02014

## **SUBJECT INDEX - 2002**

Tank Guns	ARCCB-TR-02001 ARCCB-TR-02007 ARCCB-TR-02010 ARCCB-TR-02015
Tantalum	ARCCB-TR-02008 ARCCB-TR-02011 ARCCB-TR-02014 ARCCB-TR-02016
Technical Publications	ARCCB-SP-02005
Thin Films	ARCCB-TR-02014
25-mm Gun Tubes	ARCCB-TR-02016
Ultrasonics	ARCCB-TR-02008
Ultraviolet Degradation	ARCCB-TR-02012
Venting	ARCCB-TR-02001
Vibration Absorbers	ARCCB-TR-02002 ARCCB-TR-02003
Vibrations	ARCCB-TR-02002 ARCCB-TR-02003 ARCCB-TR-02010
Wavelet Analysis	ARCCB-TR-02008
Wear	ARCCB-TR-02016
Yield Pressure	ARCCB-TR-02006
Yield Strength	ARCCB-TR-02013

## **AD NUMBERS – 2002**

<b>REPORT NUMBER</b>	<b>AD NUMBER</b>
ARCCB-TR-02001	A398 942
ARCCB-TR-02002	A399 323
ARCCB-TR-02003	A399 837
ARCCB-TR-02004	B277 840
ARCCB-SP-02005	B278 533
ARCCB-TR-02006	A402 335
ARCCB-TR-02007	A402 105
ARCCB-TR-02008	A406 403
ARCCB-TR-02009	A405 842
ARCCB-TR-02010	A405 870
ARCCB-TR-02011	A405 463
ARCCB-TR-02012	A406 089
ARCCB-TR-02013	A406 817
ARCCB-TR-02014	A408 894
ARCCB-TR-02015	A408 136
ARCCB-TR-02016	A408 856
ARCCB-TR-02017	A410 681

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
	January 2002	Final	
4. TITLE AND SUBTITLE  SONIC RAREFACTION WAVE LOW RECOIL GUN		5. FUNDING NUMBERS  AMCMS No. 6226.24.H191.1	
6. AUTHOR(S)  E. Kathe and R. Dillon			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02001	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES  This report was originally drafted for presentation at the 36 <sup>th</sup> AIAA Joint Propulsion Conference to be held in Huntsville, AL, July 2000. However, all gun related papers were removed from this conference. It was later presented at the 39 <sup>th</sup> AIAA Aerospace Sciences Meeting and Exhibit, Reno, NV, January 2001, as paper AIAA-01-0743. Therefore, the contents of this paper predate those of ARCCB-TR-01008, despite the latter's earlier publication date.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  A principal challenge faced by the U.S. Army TACOM-ARDEC Benét Laboratories in the design of armaments for lightweight future fighting vehicles with lethality overmatch is mitigating the deleterious effects of large caliber cannon recoil. The sonic RArefaction waVE low recoil gun (RAVEN) is a novel invention to dramatically reduce the gas momentum contribution to recoil with absolutely no reduction in the ballistic efficiency of launch. This technology is being investigated as part of the future combat vehicle armaments program conducted at Picatinny Arsenal, NJ, and Watervliet Arsenal, NY.			
14. SUBJECT TERMS FCS, MRAAS, Recoilless Rifle, Interior Ballistics, Propulsion, Cannon, Gun, Novel, Recoil, de Laval Nozzle, Vent			15. NUMBER OF PAGES 22
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-18  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20585.</p>			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
	February 2002	Final	
4. TITLE AND SUBTITLE		5. FUNDING NUMBERS	
<b>GUN BARREL VIBRATION ABSORBER TO INCREASE ACCURACY</b>		AMCMS No. 6226.24.H191.1	
6. AUTHOR(S) Andrew Littlefield, Eric Kathe, Robert Messier, and Kenneth Olsen			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02002	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES Presented at the 42 <sup>nd</sup> AIAA/ASME/ASCE/AHS/ASC Structures, Structural Dynamics, and Materials Conference, Seattle, WA, 16-19 April 2001. Published in proceedings of the conference.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Gun barrel vibrations lead to dispersion in the shot patterns. Thus, reducing these vibrations should lead to increased accuracy. Since the muzzle is the anti-node for all vibration modes and its vibrations have the greatest effect on shot dispersion, it is the obvious location to attempt to dampen the vibrations. A model of the gun barrel was created in MATLAB® and verified by modal impact testing. Modal impact testing was done for the barrel alone and for three different muzzle brake vibration absorber configurations. Additionally, the gun was fired with and without the absorber to determine its performance. Significant reduction in shot dispersion was observed.			
14. SUBJECT TERMS Gun Barrel, Vibrations, Accuracy, Vibration Absorber, Firing Test, Dynamics		15. NUMBER OF PAGES 19	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev 2-89)  
Prescribed by ANSI Std Z39-18  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 2 hours per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing the burden, to: Office of Information and Briefing Services, Directorate for Information Operations and Analysis, 1215 Jefferson Davis Highway, Suite 1200, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project 0704-0188, Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
	March 2002	Final	
4. TITLE AND SUBTITLE		5. FUNDING NUMBERS	
ADAPTIVE GUN BARREL VIBRATION ABSORBER		AMCMS No. 6226.24.H191.1	
6. AUTHOR(S)			
Andrew Littlefield and Eric Kathe			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)		8. PERFORMING ORGANIZATION REPORT NUMBER	
U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		ARCCB-TR-02003	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES)		10. SPONSORING/MONITORING AGENCY REPORT NUMBER	
U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			
11. SUPPLEMENTARY NOTES			
Presented at the 10 <sup>th</sup> U.S. Army Gun Dynamics Symposium, Austin, TX, 23-26 April 2001. Published in proceedings of the symposium.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT		12b. DISTRIBUTION CODE	
Approved for public release; distribution unlimited.			
13. ABSTRACT (Maximum 200 words)			
<p>Gun barrel vibrations lead to dispersion in the shot patterns. Thus, reducing these vibrations should lead to increased accuracy. Since the muzzle is the anti-node for all vibration modes and its vibrations have the greatest effect on shot dispersion, it is the obvious location to attempt to dampen the vibrations. A model of the gun barrel was created in MATLAB® and verified by modal impact testing. Modal impact testing was done for the barrel alone and for three different muzzle brake vibration absorber configurations. Significant reductions in muzzle vibrations were achieved using the vibration absorber. Methods of making the vibration absorber adaptive and models of such a system are presented.</p>			
14. SUBJECT TERMS		15. NUMBER OF PAGES	
Vibration Absorber, Passive, Smart Structures, Gun Barrels, Accuracy, Vibration, Dynamics		21	
16. PRICE CODE			
17. SECURITY CLASSIFICATION OF REPORT	18. SECURITY CLASSIFICATION OF THIS PAGE	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT
UNCLASSIFIED	UNCLASSIFIED	UNCLASSIFIED	UL

NSN 7540-01-280-5500

Standard Form 298 (Rev 2-89)  
Prescribed by ANSI Std Z39-18  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of the collection of information, including suggestions for reducing the burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4307, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
	March 2002	Final	
4. TITLE AND SUBTITLE		5. FUNDING NUMBERS	
<b>EVALUATION OF UNIVERSITY OF TENNESSEE SPACE INSTITUTE'S LASER-INDUCED SURFACE IMPROVEMENT (LISI) TECHNIQUE FOR GUN BORE PROTECTION</b>		PRON No. TU8A8F261APP	
6. AUTHOR(S) Gay Kendall, Paul J. Cote, Mark Todaro, Fang Yee, and Christopher Rickard			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02004	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Distribution limited to U.S. Government Agencies and their contractors because of critical technology; March 2002. Other requests for this document must be referred to Commander, U.S. Army Armament Research, Development, and Engineering Center, ATTN: Benet Laboratories, AMSTA-AR-CCB-TB, Watervliet, NY 12180-4050.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  This report presents results from Benet Laboratories' evaluation of 120-mm diameter smoothbore AISI 4347 steel cylinder specimens treated by the University of Tennessee Space Institute with their Laser-Induced Surface Improvement (LISI) process. The specimens were designated "100% Cr," "90% Cr/10% CrB <sub>2</sub> ," and "100% CrB <sub>2</sub> ." These designations refer merely to the compositions of the precursor coatings, and not to the compositions of the final materials, even near their surfaces. This Phase I evaluation was performed to investigate the suitability of LISI coatings for wear and erosion protection of cannon bore and/or other critical cannon surfaces. The Office of the Project Manager, Crusader (OPM-Crusader) sponsored the current study.			
14. SUBJECT TERMS Gun Bore, Gun Tube, Coatings, Laser Surface Treatment, Cannon Bore, Crusader, Chromium Coatings, Erosion		15. NUMBER OF PAGES 34	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
	April 2002	Final	
4. TITLE AND SUBTITLE INDEX TO BENET LABORATORIES TECHNICAL REPORTS – 2001			5. FUNDING NUMBERS N/A
6. AUTHORS R.D. Shuman			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-SP-02005
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) This is a compilation of technical reports published by Benet Laboratories in 2001.			
14. SUBJECT TERMS Benet Laboratories, Technical Publications, Bibliographies, Abstracts, Document Control Data			15. NUMBER OF PAGES 42
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
May 2002		Final	
4. TITLE AND SUBTITLE  YIELD PRESSURE MEASUREMENTS AND ANALYSIS FOR AUTOFRETTAGED CANNONS		5. FUNDING NUMBERS  AMCMS No. 6226.24.H180.0 PRON No. TU1E1F261ABJ	
6. AUTHORS  John H. Underwood, David B. Moak, Michael A. Audino, and Anthony P. Parker (Royal Military College of Science, Cranfield University, Swindon, UK)			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02006	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES  To be presented at the ASME Pressure Vessels and Piping Conference, Vancouver, Canada, 4-8 August 2002. To be published in proceedings of the conference.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Yield pressure for a small permanent strain was measured in quasi-static laboratory tests of autofrettaged ASTM A723 steel cannon pressure vessels. Yield pressure was found to be a consistent ratio of the yield strength measured in close proximity to the area of observed yielding. Comparable yield pressure measurements for cannons firing with typical 5-ms pressure pulse duration gave 14% higher yield pressures, attributed to strain-rate effects on plastic deformation.  Calculated von Mises' yield pressure for the laboratory test conditions, including the Bauschinger-modified inner diameter residual stress and open-end vessel conditions, agreed with measured yield pressure within 3 to 5 %. Calculated yield pressure was found to be insensitive to the value of axial residual stress, since it is typically the intermediate value in the von Mises' yield criterion.  A description of yield pressure normalized by yield strength was given for autofrettaged A723 open-end pressure vessels over a range of wall ratio and degree of autofrettage, including effects of Bauschinger-modified residual stress. This method for calculating yield pressure is proposed as a design procedure for cannons and other pressure vessels.			
14. SUBJECT TERMS  Yield Pressure, Cannons, Yield Strength, High-Strength Steels, Autofrettage, Bauschinger Effect		15. NUMBER OF PAGES 12	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE May 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE A FIRE OUT-OF-BATTERY TANK GUN: THEORY AND SIMULATION			5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. 4A1C1FYA1ABJ
6. AUTHORS E. Kathe and R. Gast			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4050			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-02007
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES Presented at the 10 <sup>th</sup> U.S. Army Gun Dynamics Symposium, Austin, TX, 23-26 April 2001. Published in proceedings of the symposium.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) As part of the <i>Army After Next</i> effort, TACOM-ARDEC's Benet Laboratories undertook a radical departure from current tank gun recoil to engineer a soft recoil tank gun. Such a leap in technology may be required to enable a lightweight future combat system to withstand the recoil imparted by a large caliber gun, especially during fire on the move. Although soft recoil is not new to smaller caliber guns and howitzers, implementation for a large caliber tank gun is unprecedented. The theoretical foundations of this recoil management technology will be presented here. Experimental test results from a 105-mm fire out-of-battery tank gun demonstrator will be presented in a separate report.			
14. SUBJECT TERMS Gun Mount, Soft Recoil, Fire Out-of-Battery, Future Combat System			15. NUMBER OF PAGES 20
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE July 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE AN ALGORITHM FOR THE DETERMINATION OF COATING PROPERTIES FROM LASER-GENERATED AND DETECTED RAYLEIGH WAVES USING WAVELET ANALYSIS: APPLICATION TO SPUTTERED TANTALUM			5. FUNDING NUMBERS AMCMS No. 6226.24.H191.1
6. AUTHORS M.A. Doxbeck, M.A. Hussain, J. Rama, A. Abbate (Panametrics, Inc., Waltham, MA), And J. Frankel			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-02008
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES Presented at the Annual Review of Progress in Quantitative Nondestructive Evaluation, Brunswick, ME, 29 July to 3 August 2001. Published in the <i>Review of Progress in Quantitative Nondestructive Evaluation</i> .			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) We used single-source and single-detector laser-ultrasonic measurements to generate and detect Rayleigh waves on tantalum sputtered steel substrates. Group velocity dispersion curves were calculated from the single-detected signals using wavelet techniques. Theoretical dispersion curves were calculated via the Achenbach and Keshava analysis. A simplex minimization technique between theory and experiment, using known values for the substrate, allowed us to evaluate the coating parameters. The coating thickness was measured accurately with micrometers, and gives the most easily available comparisons with the output of the simplex method. The results using the straightforward wavelet method were compared with an adaptation thereof.			
14. SUBJECT TERMS Algorithm, Coatings, Lasers, Ultrasonics, Rayleigh Waves, Wavelet Analysis, Sputtered Tantalum			15. NUMBER OF PAGES 11
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE August 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE CHARACTERIZATION OF STEELS USING A REVISED KINETIC HARDENING MODEL INCORPORATING BAUSCHINGER EFFECT			5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. TU1G1F261ABJ
6. AUTHORS Anthony P. Parker (Royal Military College of Science, Cranfield University, Swindon, UK), Edward Troiano, John H. Underwood, and Charles Mossey			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-02009
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES To be presented at Gun Tubes Conference 2002, Kable College, Oxford, UK, 15-18 September 2002. To be published by ASME Journal of Pressure Vessel Technology.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) A new variant of the nonlinear kinematic hardening model is proposed that accommodates both nonlinear and linear strain hardening during initial tensile loading and reduced elastic modulus during initial load reversal. It also incorporates the Bauschinger effect, as a function of prior tensile plastic strain, during the nonlinear compressive loading phase. The model is shown to fit experimental data from a total of five candidate gun steels. The numerical fits will be employed in subsequent work to predict residual stresses and fatigue lifetimes for autofrettaged tubes manufactured from the candidate steels.			
14. SUBJECT TERMS Kinetic Hardening Model, Elastic Modulus, Bauschinger Effect, Autofrettage, Steels, A723 Steel, HY180 Steel, PH 13-8 Mo Steels, Residual Stress, Pressure Vessels, Gun Tubes			15. NUMBER OF PAGES 16
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE August 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE  DYNAMICALLY TUNED SHROUD FOR ATTENUATING GUN BARREL VIBRATION		5. FUNDING NUMBERS  AMCMS No. 6226.24.H180.0 PRON No. 4A1C1FYA1ABJ	
6. AUTHORS  A.G. Littlefield, E.L. Kathe, and R. Durocher			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02010	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES  Presented at the SPIE 7 <sup>th</sup> Annual International Symposium on Smart Structures and Materials, San Diego, CA, 17-21 March 2002. Published in proceedings of the symposium.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Modern tank guns, such as the one on the Abrams, are stabilized to allow fire on the move while traversing uneven terrain. The current barrel is short enough that treating it as a rigid beam allows engagement of another tank at ranges of over a kilometer. However, as the length of the tube is extended, to meet required muzzle exit velocities, the terrain-induced vibrations lead to increased muzzle pointing errors. A method to reduce these vibrations is to use the forward thermal shroud as part of a mass tuned damper. In this case the system under study is an extended length version of the gun currently fielded. This extended length increases its susceptibility to terrain-induced vibrations. The forward thermal shroud has been shortened and additional mass has been added onto its forward collar. This collar is then supported by springs, which are preloaded so that they stay in contact through the full range of the shroud's movement. Varying the stiffness of these springs allows for tuning of the absorber. Different types of springs and attachments have been tried. The current version uses leaf springs and a wedge collar. This system has been modeled, and experiments have been conducted to validate the model.			
14. SUBJECT TERMS  Vibrations, Vibration Absorber, Cannons, Gun Barrel, Passive, Accuracy, Dynamics		15. NUMBER OF PAGES 17	
		16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE August 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE EVOLUTION OF SURFACE STRUCTURES IN SPUTTERED COATINGS			5. FUNDING NUMBERS AMCMS No. 6111.02.H671.1
6. AUTHORS Mark A. Johnson and Paul J. Cote			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-02011
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES Presented at the 6 <sup>th</sup> World Multiconference on Systemics, Cybernetics, and Informatics, Orlando, FL, 14-18 July 2002. Published in Proceedings of the IIS World Multiconference on Image, Acoustic, Speech, and Signal Processing.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) The evolving surface structure of sputtered tantalum and niobium coatings was characterized in terms of dynamic scaling exponents using atomic force microscopy (AFM) to map surface structures over a range of scales from 10-nm to 5-Cm. New numerical techniques are introduced to systematically determine the time evolution of the spatial scaling parameters associated with the coating surface morphology. These dynamic scaling parameters define a unique <i>universality class</i> that is associated with the deposition process, and provides insight into the dynamics of the growth processes of thick metal films.			
14. SUBJECT TERMS Image Processing, Universality Class, Dynamic Scaling Exponents, Fractals			15. NUMBER OF PAGES 13
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Service, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE	3. REPORT TYPE AND DATES COVERED	
August 2002		Final	
4. TITLE AND SUBTITLE  DETRENDED FLUCTUATION ANALYSIS OF UV DEGRADATION IN A POLYURETHANE COATING		5. FUNDING NUMBERS  AMCMS No. 6226.24.H180.0 PRON No. MIPR1PICTNY0	
6. AUTHORS  Mark A. Johnson and Paul J. Cote			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02012	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07805-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES  Submitted to <i>Journal of Coatings Technology</i> .			
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  Changes in the intrinsic structure of paint surfaces resulting from extended UV exposure can significantly alter the appearance of the paint due to a breakdown in the resin that binds the fine paint particulates. In this study, the coating structure of a solvent-based polyurethane was analyzed to establish correlations between the intrinsic spatial scaling properties of the coating and UV exposure time. Atomic force microscopy (AFM) and laser scanning confocal microscopy (LSCM) were employed to map surface structures over a range of scales from 100-nm to 100- $\mu$ m. The roughness of the polyurethane surface was characterized in terms of scaling exponents by quantifying the local roughness using detrended fluctuation analysis (DFA) to identify long-range power-law correlations and correct for inhomogeneities in the surface structure. This approach provides a means to directly compare AFM and LSCM results over a range of scales consistent with those of a self-affine fractal. The time-dependent dynamics of the roughening process was also determined in order to provide a metric for characterizing the evolving surface morphology. The results provide fresh insight into the mechanisms of polyurethane coating degradation under UV exposure.			
14. SUBJECT TERMS  Detrended Fluctuation Analysis, UV Degradation, Image Analysis, Fractals			15. NUMBER OF PAGES  15
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT  UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE  UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT  UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE September 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE  SAFE MAXIMUM PRESSURE DETERMINATION FOR THE M829E3/M256 CANNON QUALIFICATION PROGRAM			5. FUNDING NUMBERS  AMCMS No. 6436.53.B991.2 PRON No. 4A1E1FYA1ABJ
6. AUTHORS  David C. Smith and Eugene E. Coppola			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000			8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02013
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  The M256 120-mm cannon is the main armament of the M1A1 and M1A2 tanks. With the increased pressure generated by the latest version of the M829 APFSDS-T cartridge (A3), the yield strength of the cannon would have been insufficient to prevent elastic deformation of the tube. Classical theory indicated that this pressure could not have been contained, but it was known that the theory is somewhat conservative. By testing to elastic deformation and using statistical analysis, a new Safe Maximum Pressure (SMP) as defined by NATO Standardization Agreement (STANAG) 4110, was determined. This resulted in the M256 tube yield strength being redefined and capable of firing the M829A3.			
14. SUBJECT TERMS  M256, Cannon, Test, Yield, Yield Strength, Safe Maximum Pressure, Hydraulic, Strain Rate			15. NUMBER OF PAGES 15
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE October 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE <i>IN-SITU PHASE EVOLUTION STUDY IN MAGNETRON-SPUTTERED TANTALUM THIN FILMS</i>			5. FUNDING NUMBERS AMCAMS No. 6111.02.H671.1
6. AUTHORS S.L. Lee, D. Windover (RPI, Troy, NY), T.-M. Lu (RPI), and M. Audino			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-02014
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES Presented at the International Conference on Metallurgical Coatings and Thin Films, San Diego, CA, 22-26 April 2002. Published in <i>Metallurgical Coatings and Thin Films</i> .			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) The design and construction of a planar magnetron-sputter deposition system with a beryllium chamber was accomplished to perform <i>in-situ</i> x-ray diffraction growth study of refractory coatings. The deposition system was set on top of a laboratory $\theta$ - $2\theta$ x-ray diffractometer. A two-dimensional array detector was interfaced for observation of the Debye rings during growth. Integration along the $2\theta$ and $\chi$ directions allows fast phase and texture determination. The system was built to study effects of sputter deposition parameters on the structural properties of tantalum on steel, silicon, and glass substrates without exposing the system to atmosphere pressure.			
<p>Two sputter depositions of tantalum films onto glass substrate in argon gas are reported here, one was deposited at 25-mm target-detector distance, 3.9 Pascal argon gas, and the other at 108-mm target-detector distance and 1.3 Pascal argon gas. The first film grew to 250-nm in 39 minutes at an average growth rate of 6.4-nm/minute. It consisted of 45-nm of interface layer, which showed no crystalline structure, and was most likely amorphous film. It was followed by 15-nm growth of <math>\beta</math>-tantalum, and then followed by 190-nm growth of <math>\alpha</math>-tantalum. From the full-width half maximum of the <math>\chi</math>-plot, it was determined that the <math>\beta</math>-tantalum region was &lt;002&gt; textured, and the <math>\alpha</math>-tantalum region was &lt;110&gt; textured, and grew more textured with deposition time. The second film grew to 36-nm in 22 minutes at an average growth rate of 1.6-nm/minute. It consisted of 31-nm of layer, which showed no crystalline structure, and was most likely amorphous film. It was followed by 5-nm of surface layer of <math>\beta</math>- and <math>\alpha</math>-tantalum. <i>Ex-situ</i> grazing incidence x-ray diffraction performed on the film surface confirmed the <i>in-situ</i> results. <i>Ex-situ</i> pole figure analysis showed &lt;110&gt; fiber texture in <math>\alpha</math>-tantalum, and highly &lt;002&gt; texture in <math>\beta</math>-tantalum.</p>			
14. SUBJECT TERMS <i>In-Situ Characterization, Magnetron Sputtering, Real-Time X-Ray Diffraction, Tantalum, Two-Dimensional Detector</i>			15. NUMBER OF PAGES 18
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE October 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE  MAIN BATTLE TANK FLEXIBLE GUN TUBE DISTURBANCE MODEL: THREE-SEGMENT MODEL		5. FUNDING NUMBERS  Sales Order No. 2WHR-BV	
6. AUTHORS  Henry J. Sneed			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000		8. PERFORMING ORGANIZATION REPORT NUMBER  ARCCB-TR-02015	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES)  U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000		10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES  Presented at the 10 <sup>th</sup> U.S. Army Gun Dynamics Symposium, Austin, TX, 23-26 April 2001. Published in proceedings of the symposium.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT  Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  A rational approach to disturbance rejection is proposed and applied to a simple three degree-of-freedom flexible gun tube model using feedforward and feedback compensation. The first two natural frequencies of the pin-free and cantilever tube are matched by adjusting the dimensions of the rigid segments and the stiffness of the torsional springs that join them. It was found that, contrary to the previously analyzed two degree-of-freedom segment model, the muzzle-end segment could be stabilized by the proper choice of transfer functions and elevation driveline response. The analysis serves to establish the requirements for the transfer functions and stabilizing actuator systems.			
14. SUBJECT TERMS  Gun Tube, Flexible, Stabilization		15. NUMBER OF PAGES  22	16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT  UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE  UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT  UNCLASSIFIED	20. LIMITATION OF ABSTRACT  UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE November 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE CHARACTERIZATION OF EXPLOSIVELY BONDED AND FIRED TANTALUM LINERS APPLIED TO 25-MM GUN TUBES			5. FUNDING NUMBERS AMCMS No. 6226.24.H191.1
6. AUTHORS C. Mulligan, M. Audino, P. Cote, G. Kendall, C. Rickard, S. Smith, and M. Todaro			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-02016
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.		12b. DISTRIBUTION CODE	
<b>13. ABSTRACT (Maximum 200 words)</b> Characterization analyses were conducted on sections taken from three truncated 25-mm gun tubes that were explosively bonded with pure tantalum. Two of the barrels had been test fired and one was received in the pre-fired condition. The two test-fired tubes consist of one smoothbore design and one no-twist rifled bore design. The specimen received in the pre-fired condition was the smoothbore design. Characterization work included macroscopic examination, liner thickness measurements, microstructural analysis, microhardness testing, adhesion testing, scanning electron microscopy, energy dispersive spectroscopy, wavelength dispersive spectroscopy, hydrogen analysis, and pulsed laser heating. Characterization results indicate vast improvement over the erosion characteristics of standard nitrided 25-mm Bushmaster gun tubes when firing the unfilled, original M919 propellant (100% HE 9053). Some areas of concern in the performance of the liner include heavy heat-check cracking, severe gas erosion, high concentration levels of hydrogen, and surface oxidation of the tantalum liners.			
14. SUBJECT TERMS Explosive Bonding, Tantalum, 25-mm Gun Tubes, Wear, Erosion, Refractory Coatings			15. NUMBER OF PAGES 40
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188
<p>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</p>			
1. AGENCY USE ONLY (Leave Blank)	2. REPORT DATE December 2002	3. REPORT TYPE AND DATES COVERED Final	
4. TITLE AND SUBTITLE UPDATED EROSION MODELING PREDICTIONS FOR THE M829E3 ROUND			5. FUNDING NUMBERS AMCMS No. 6226.24.H180.0 PRON No. 4AZC2FYK1ABJ
6. AUTHORS S. Sopok, G. Pflegl, and C. Rickard			
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Benet Laboratories, AMSTA-AR-CCB-O Watervliet, NY 12189-4000			8. PERFORMING ORGANIZATION REPORT NUMBER ARCCB-TR-02017
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army ARDEC Close Combat Armaments Center Picatinny Arsenal, NJ 07806-5000			10. SPONSORING / MONITORING AGENCY REPORT NUMBER
11. SUPPLEMENTARY NOTES Presented at the 38 <sup>th</sup> JANNAF Combustion Meeting, Destin, FL, 8-12 April 2002. Published in proceedings of the meeting.			
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12b. DISTRIBUTION CODE
13. ABSTRACT (Maximum 200 words) Erosion modeling predictions are given for the current M829E3 round configuration and weighted averages per temperature for the computer correction factor (CCF). Our gun erosion model was developed through a ten-year joint partnership with Software and Engineering Associates, Inc., Carson City, NV. These predictions are based on recent cannon characterization data. These latest predictions include significant changes in propellant configuration and projectile weight that were made to the current M829E3 configuration compared to our initially presented M829E3 modeling predictions two years ago. For the last two years, additional nonablative M829E3 erosion modeling predictions have not been conducted or presented. This was due to a diversion of erosion modeling resources toward ablative M829E3 erosion predictions and erosion predictions related to the selection of six M256 cannons for M829E3-related fatigue testing. For the current M829E3 configuration, these changes in gas pressure, gas temperature, gas velocity, and increased projectile weight collectively contributed to a predicted increase in M256 cannon erosion life compared to our initially presented M829E3 modeling effort. In addition, the current set of M829E3 weighted averages per temperature for CCF from Fort Knox (19% hot 49°C/120°F, 64% basic 21°C/70°F, 16% cold -7°C/20°F, and 1% severe -32°C/-25°F) collectively contributed to a further predicted increase in M256 cannon erosion life compared to the two-year-old set of weighted averages per temperature (33% hot, 33% basic, 0% cold, and 33% severe). For the current predictions, the peak eroded cannon axial position remains at approximately 60 inches from the rear face of the tube ±6 inches; and this position dictates the erosion life of the cannon. Erosion life predictions at this position are given for each of the round-conditioning temperatures and the Fort Knox mixture of round-conditioning temperatures. At this peak eroded position, the respective 49°C/120°F, 21°C/70°F, -7°C/20°F, -32°C/-25°F, and Fort Knox mixture round-conditioning temperature cases have predicted erosion lives of approximately 183, 287, 388, 302, and 269 rounds. The mixture of M829E3 rounds with some types of HEAT and slug rounds significantly moves the peak eroded axial position up-bore to the bore onset region.			
14. SUBJECT TERMS Erosion Modeling, M256 Cannon, M829E3 Round, Erosion Predictions			15. NUMBER OF PAGES 17
			16. PRICE CODE
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL

NSN 7540-01-280-5500

Standard Form 298 (Rev. 2-89)  
Prescribed by ANSI Std. Z39-1  
298-102

---

TECHNICAL REPORT INTERNAL DISTRIBUTION LIST

	<u>NO. OF COPIES</u>
TECHNICAL LIBRARY ATTN: AMSTA-AR-CCB-O	1
TECHNICAL PUBLICATIONS & EDITING SECTION ATTN: AMSTA-AR-CCB-O	3
PRODUCTION PLANNING & CONTROL DIVISION ATTN: AMSTA-WV-ODP-Q, BLDG. 35	1

NOTE: PLEASE NOTIFY DIRECTOR, BENÉT LABORATORIES, ATTN: AMSTA-AR-CCB-O OF ADDRESS CHANGES.

---

---

TECHNICAL REPORT EXTERNAL DISTRIBUTION LIST

<u>NO. OF COPIES</u>	<u>NO. OF COPIES</u>		
DEFENSE TECHNICAL INFO CENTER ATTN: DTIC-OCA (ACQUISITIONS) 8725 JOHN J. KINGMAN ROAD STE 0944 FT. BELVOIR, VA 22060-6218	2	COMMANDER U.S. ARMY RESEARCH OFFICE ATTN: TECHNICAL LIBRARIAN P.O. BOX 12211 4300 S. MIAMI BOULEVARD RESEARCH TRIANGLE PARK, NC 27709-2211	1
COMMANDER U.S. ARMY ARDEC ATTN: AMSTA-AR-WEE, BLDG. 3022 AMSTA-AR-AET-O, BLDG. 183 AMSTA-AR-FSA, BLDG. 61 AMSTA-AR-FSX AMSTA-AR-FSA-M, BLDG. 61 SO AMSTA-AR-WEL-TL, BLDG. 59	1 1 1 1 1 2	COMMANDER ROCK ISLAND ARSENAL ATTN: SIORI-SEM-L ROCK ISLAND, IL 61299-5001	1
PICATINNY ARSENAL, NJ 07806-5000		COMMANDER U.S. ARMY TANK-AUTMV R&D COMMAND ATTN: AMSTA-DDL (TECH LIBRARY) WARREN, MI 48397-5000	1
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-DD-T, BLDG. 305 ABERDEEN PROVING GROUND, MD 21005-5066	1	COMMANDER U.S. MILITARY ACADEMY ATTN: DEPT OF CIVIL & MECH ENGR WEST POINT, NY 10966-1792	1
DIRECTOR U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-WM-MB (DR. B. BURNS) ABERDEEN PROVING GROUND, MD 21005-5066	1	U.S. ARMY AVIATION AND MISSILE COM REDSTONE SCIENTIFIC INFO CENTER ATTN: AMSAM-RD-OB-R (DOCUMENTS) REDSTONE ARSENAL, AL 35898-5000	2
CHIEF COMPOSITES & LIGHTWEIGHT STRUCTURES WEAPONS & MATLS RESEARCH DIRECT U.S. ARMY RESEARCH LABORATORY ATTN: AMSRL-WM-MB (DR. BRUCE FINK) ABERDEEN PROVING GROUND, MD 21005-5066	1	NATIONAL GROUND INTELLIGENCE CTR ATTN: DRXST-SD 2055 BOULDERS ROAD CHARLOTTESVILLE, VA 22911-8318	1

---

NOTE: PLEASE NOTIFY COMMANDER, ARMAMENT RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER,  
BENÉT LABORATORIES, CCAC, U.S. ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND,  
AMSTA-AR-CCB-O, WATERVLIET, NY 12189-4050 OF ADDRESS CHANGES.

---

DEPARTMENT OF THE ARMY  
ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER  
BENÉT LABORATORIES, CCAC  
US ARMY TANK-AUTOMOTIVE AND ARMAMENTS COMMAND  
WATERVLIET, NY 12189-4000

OFFICIAL BUSINESS  
AMSTA-AR-CCB-O  
TECHNICAL LIBRARY